



The ECMO smart canula®

Next generation design for superior performance




The virtually wall-less *smart canula*® applied as temporary caval stent drains collateral blood flow at all affluent levels :
Unmatched venous drainage results!

No 1609




smart canula® and a standard cannula



Suction required with remote 19F access

Ordering information for typical *ECMO smart canula*® configurations



Catalog Numbers*	Connecting Diameter Inch	Guide-wire Inch	Tubing Length mm	Covered Length mm	Uncovered Length mm	Diameter/Size Collapsed / Expanded F F	Intra-vascular Maximal length mm	Total Length mm
V 1/4 20 220 STC	1/4	.035	100	40	80	<15 20	120	220
V 1/4 20 260 STC	1/4	.035	100	40	120	<15 20	160	260
V 1/4 20 340 STC	1/4	.035	100	40	200	<15 20	240	340
V 1/4 20 430 STC	1/4	.035	100	40	290	<15 20	330	430
V 1/4 20 530 STC	1/4	.035	100	40	390	<15 20	430	530
V 3/8 24 220 STC	3/8	.035	100	80	40	<18 24	120	220
V 3/8 24 260 STC	3/8	.035	100	80	80	<18 24	160	260
V 3/8 24 340 STC	3/8	.035	100	80	160	<18 24	240	340
V 3/8 24 430 STC	3/8	.035	100	80	250	<18 24	330	430
V 3/8 24 530 STC	3/8	.035	100	80	350	<18 24	430	530
V 3/8 24 630 STC	3/8	.035	100	100	430	<18 24	530	630
V 3/8 24 680 STC	3/8	.035	100	170	410	<18 24	580	680
V 3/8 24 730 STC	3/8	.035	100	170	460	<18 24	630	730

For more information, contact your local *smart canula*® sales representative

*ordering numbers include *smartcanula*® specific mandrel for collapsed insertion

device specifications may change at any time without prior notice